


**26"**  
TileVision®

External Dimensions (W x H x D)		685 x 450 x 92 mm
Weight (Screen & Back Box)		20Kg (44.09 lb)
Power	AC/DC Adaptor	AC 100–240V, 50/60 Hz/24VDC/5.42A adaptor
	Consumption	Max. 72W, Standby below 3W
System	Analog	PAL-BG, I, DK/SECAM-BG, DK, L
	Digital	DVB-T (MHEG-5) MPEG-2 decoding
TV	Programme	VHF 2–13, UHF 21–69, Cable S1–S41
		FVS 100 programme (Analog)
LCD	Size	26" (660 mm) Diagonal – Widescreen (16:9)
	Resolution/Type	WXGA (1366 x 768) a-si TFT active matrix
	Brightness	450 cd/m2
	Contrast Ratio	4,000:1
	Viewing Angle	89°/89°/89°/89° (L/R/U/D)
	Colour Depth	8 bits (16.77 million colours)
	Response Time	8 ms (Typ)
Audio	Output	3W + 3W RMS
	System	Nicam, A2 Stereo
Connections		EURO-SCART (Full), HDMI, S-Video, PC RGB, Component and Composite Video, Audio L/R, PC Audio In, Audio Out (Headphones), Speakers, Antenna/Tuner (Co-axial)
Control		RS-232 Port for Home Automation Systems, Infrared Link In & Out to interface with external equipment, RJ12 Port for Interactive Hotel TV System integration, Sky™ Remote Link to control a Sky™ box via the TileVision®
Features		Auto and Manual Programme, Aspect Ratio Control, Picture and Sound Memory, Teletext TOP/FLOP/MHEG-5 Teletext, Quick View, Real Time Clock
Accessories		Waterproof R/C with Holder, Standard R/C, Installation/Operating Instructions, Power Cord, DC Adaptor, Stereo Speaker & Cable, Back Box, Acrylic Bezel



**19"**  
TileVision®

External Dimensions (W x H x D)		483 x 353 x 75 mm
Weight (Screen & Back Box)		12Kg (26.5 lb)
Power	AC/DC Adaptor	AC 100–240V, 50/60 Hz/12VDC/6.67A adaptor
	Consumption	Max. 50 W, Standby below 3 W
System	Analog	PAL-BG, I, DK/SECAM-BG, DK, L
	Digital	DVB-T (MHEG-5) MPEG-2 decoding
TV	Programme	VHF 2–13, UHF 21–69, Cable S1–S41
		FVS 100 programme (Analog)
LCD	Size	19" (480 mm) Diagonal – Widescreen (16:9)
	Resolution/Type	WXGA (1440 x 900) a-si TFT active matrix
	Brightness	300 cd/m2
	Contrast Ratio	1,000:1
	Viewing Angle	85°/85°/80°/80° (L/R/U/D)
	Colour Depth	16.77 million colours (6 bit + Hi-FRC)
	Response Time	5 ms
Audio	Output	3W + 3W RMS
	System	Nicam, A2 Stereo
Connections		EURO-SCART (Full), HDMI, S-Video, PC RGB, Component and Composite Video, Audio L/R, PC Audio In, Audio Out (Headphones), Speakers, Antenna/Tuner (Co-axial)
Control		RS-232 Port for Home Automation Systems, Infrared Link In & Out to interface with external equipment, RJ12 Port for Interactive Hotel TV System integration, Sky™ Remote Link to control a Sky™ box via the TileVision®
Features		Auto and Manual Programme, Aspect Ratio Control, Picture and Sound Memory, Teletext TOP/FLOP/MHEG-5 Teletext, Quick View, Real Time Clock
Accessories		Waterproof R/C with Holder, Standard R/C, Installation/Operating Instructions, Power Cord, DC Adaptor, Stereo Speaker & Cable, Back Box, Acrylic Bezel

# TILEVISION®

*the bathroom television*



**19" and 26" waterproof LCD TVs**

# No new bathroom is complete without a **TILEVISION®**

A TileVision® is a completely independent digital television – totally waterproof (IP65) and totally tamperproof.

The heated 6 mm safety glass screen keeps the picture clear of condensation, making TileVision® perfect for use in high humidity areas such as bathrooms.

All functions, including setup and tuning are performed using the waterproof remote control.

As well as receiving all free-to-view digital TV and radio with digital text, a TileVision® is fully compatible with Sky™ Remote Link, Multi-room AV systems and Hotel television networks via RS-232 and RJ12 connectors.



**Available in Black, Mirror or Silver finish, the 19" and 26" televisions feature:**

- Widescreen (16:9) TFT LCD screens
- DVB-T digital tuner receives all free-to-view television and radio
- Digital text and Interactive services (MHEG-5) via the red button
- Perfect picture from high brightness, high contrast LCD screens
- Ultra wide viewing angles ensure high picture quality from any position
- Superb sound through water resistant, flush mount, single stereo speaker
- Analogue tuner with Teletext and Fast Text
- HDMI connector for High Definition (HD) input plus SCART, Component, Composite and S-Video
- Built in Sky™ Remote Control Link to control the satellite receiver via the coaxial aerial cable
- Infrared Link in and out to allow interface with external equipment (DVD, STB etc.)
- Waterproof remote control with self-adhesive holder

