

# TILEVISION<sup>®</sup>

*the bathroom television*



27" waterproof LCD TVs





# No new bathroom is complete without a TILEVISION

A TileVision® is a completely independent digital television – totally waterproof (IP65) and totally tamperproof.

The heated 6 mm safety glass screen keeps the picture clear of condensation, making TileVision® perfect for use in high humidity areas such as bathrooms.

All functions, including setup and tuning are performed using the splashproof learning remote control.

As well as receiving both digital TV & analogue TV, a TileVision® is fully compatible with Sky™ Remote Link, Multi-room AV systems and Hotel television networks via RS-232 and RJ12 connectors.



Available in Black or Mirror finish, the 27" television features:

- DVB-T digital tuner receives all free-to-view television and radio
- Digital text and Interactive services (MHEG-5) via the red button
- Analogue tuner with Teletext and Fast Text
- Perfect picture from high brightness, high contrast LCD screens
- Ultra wide viewing angles ensure high picture quality from any position
- Superb sound through water resistant, flush mount, single stereo speaker
- Three HDMI connectors for High Definition (HD) input plus SCART, Component, Composite, VGA (D-SUB) input
- PVR (Personal Video Recorder) function & Multimedia play back
- Built in Sky™ Remote Control Link to control the Sky™ satellite receiver via the coaxial aerial cable
- Infrared Link in and out to interface with external equipment (DVD, STB etc.)
- Universal splashproof learning remote control with self-adhesive holder

# s p e c i f i c a t i o n s

27" Display	Screen Size	27" (685 mm) Diagonal
	Resolution	1920 x 1080 Full HD
	Type	a-si TFT LCD Module with W-LED Backlight System
	Brightness	300 cd/m <sup>2</sup>
	Contrast Ratio	3,000:1
	Viewing Angle	89°/89°/89°/89° - L/R/U/D
	Colour Depth	16.7M colours (RGB 8 bits)
Power	Response Time	12 ms
	AC/DC Adaptor 4M Lead	Input 100-240 VAC 50/60 Hz, Output 24 VDC/3.75 A
	Consumption	70W max
Dimensions/ Weight	Standby	Less than 1 watt
	External Dimensions (W x H x D)	685 mm x 450 mm x 75 mm
	Cutout/Recess Required	703 mm x 455 mm and 75 mm
	Mirrored Acrylic Surround	Overall size 728 mm x 494 mm (1.5 mm deep, 30 mm wide)
	Total Weight including Back Box	22.5 Kg

Tuner/ Reception	Digital TV	DVB-T (MHEG-5) MPEG-2, H.264/MPEG-4
	Analogue TV	PAL-BG, I, DK/SECAM-BG, DK, L
Audio	Channels	DTV 600, ATV 100
	Output	8W + 8W @ 8Ω
Connectivity	Features	Surround Sound, Treble and Bass Controls
	Aerial Input	75 ohm coaxial
	HDMI	3 x HDMI Ports 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
	Component (Y,Pb,Pr)	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
	SCART	Full Scart
	PC RGB (D-sub) Format	Up to 1920 x 1080 @ 60Hz
	PC RGB (D-sub) Colour	16 Bit, 24 Bit, 32 Bit
	Composite (CVBS)	1.0Vp-p +/-5%
	Common Interface Port	Additional channels via CAM/Smartcard
	L+R Audio Input	For Component and Composite (CVBS) Audio Input
	PC Audio Input	1 x Stereo Jack Socket for PC Audio Input
	Headphone Out	Headphone
Control	Speaker	Clip Terminals LEFT +/- and RIGHT +/-
	RS-232	Receives RS232 Control Codes from Home Automation/Hotel Systems
	Sky™ IR Link	Control of a Sky Box via the TileVision® IR receiver and Aerial cable
	RJ12	Command code in and out
Loudspeaker	3.5mm IR In	For connection to external IR receiver
	3.5mm IR Out	For connection to external IR emitter
	Loudspeaker	6.5" Single Stereo, Flush Mount, 8 ohm, Water Resistant
	Speaker External Dimensions	240 mm Ø x 95 mm deep
Accessories	Speaker Cutout Required	208 mm Ø
	Speaker Depth	79 mm
	Splashproof Remote Control	Universal Learning, Full Function, complete with battery
	Remote Control Holder	Wall/Tile mount, clear plastic with gel adhesive strip
	Standard Remote Control	Complete with batteries
	Stainless Steel Back Box	Adjustable brackets to allow precise installation flush with tiles/wall
	Mains Power Cord	UK and Europe
	AC/DC Adaptor	Complete with detachable 4 meter cord
Convenience Features	AC / DC Adaptor Dimensions	170mm x 65mm x 38mm depth (excluding connecting cables)
	Speaker Cable	4.5 meter, 4 core, colour coded
	Installation and Operating Instructions	Book
	Multi- Language OSD	Dansk, Deutsch, English, Español, Français, Italiano, Magyar, Nederlands, Polski, Português, Slovenščina.
	Auto Tuning	DTV and ATV
	Manual Tune	DTV and ATV
	Programme Edit	Allows programmes to be deleted, skipped, or selected as favourites
	Favourites List	Favourite channels can be stored and accessed in a favourites list
	EPG	8 day Electronic Programme Guide
	Picture Mode	Standard, Mild, Dynamic, User
Hotel Mode	Sound Mode	Standard, Music, Movie, Sports, User
	Aspect Ratio Control (ARC)	Auto, Zoom 1, Zoom 2, 16:9, 4:3
	AVL	Auto Volume Leveller
	Subtitles	Switchable, as available from the broadcaster
	Digital Text	MHEG 5 - Interactive text via the red button
	Analogue Teletext	TOP/FLOF
	Volume Limit	Set maximum volume limit
	Input Selection	Selects which Inputs will be available on the Input Menu
	Input Priority	Selects which Input will be the default when the TileVision® is turned on
	Menu Button Disabled	Menu button can be disabled to prevent access to menus by hotel guest